

Equipos domésticos / Domestic equipment
DANNA 30

Ref.	Descripción / Description
DDANA	Descalcificador Danna 30 TM68C3 30L Danna 30 water softener TM68C3 30 L.

Datos técnicos:

- Volumen: 30 litros
- Consumo de sal: 3,5 kg
- Caudal: 1,75 m³/h
- Material del cabinet: PE soplado de alta resistencia
- Botella de poliéster reforzada con fibra de vidrio
- Válvula de disco cerámico
- Conexión de 1"
- Presión mínima de trabajo: 2 kg/cm²
- Presión máxima de trabajo: 7 kg/cm²
- Temperatura de trabajo entre 2 °C y 35 °C
- Resina monoesférica calidad alimentaria
- Mezclador de dureza
- Regeneración contracorriente
- Display digital inteligente
- Dimensiones:
a. 990 mm | b. 290 mm | c. 525 mm

Features:

- Volume: 30 liters
- Salt consumption: 3,5 kg
- Flow rate: 1,75 m³/h
- Cabinet material: High PE blow strength
- Fiberglass reinforced polyester bottle
- Ceramic disc valve
- 1" connection
- Minimum working pressure: 2 kg/cm²
- Maximum working pressure: 7 kg/cm²
- Working temperature between 2 ~ 35 °C
- Resin monospheric food grade
- Hardness mixer
- Countercurrent regeneration
- Smart digital display
- Dimensions:
a. 990 mm | b. 290 mm | c. 525 mm



Resina monoesférica que aumenta el rendimiento
Monosphere resin that increases performance



Bypass con válvula reguladora de dureza
Bypass with hardness regulating valve



Botella presurizada certificada por NSF
NSF certified pressurized bottle



Boya de seguridad para prevenir fugas de agua
Safety buoy to prevent water leaks



Válvula contracorriente. Ahorro de agua y sal
Counterflow valve. Saving water and salt



Cabinet fabricado en polietileno alta resistencia
Cabinet made of high resistance polyethylene




Bandeja separadora de salmuera
Brine separator tray



Clips de seguridad
Safety clips



Diseño exclusivo y elegante
Exclusive and elegant design



* Dimensiones aproximadas en mm.
Approximate dimensions in mm.